





DATA SHEET

SPECIFICATIONS

WEIGHT	4450 lbs.
LENGTH	6 ft. 9 in.
WIDTH	6 ft. 4 in.
HEIGHT	4 ft. 3 in.
PROCESS RATE	500 GPM
TOTAL SCREENING AREA	24 ft ²
# OF SCREENS	3
SCREEN TYPE	Pre-tensioned
SCREEN SIZE	25.13" x 49.3"

➤ Available in XP or NON-XP
Skids can be customized for effortless integration

-  **DUAL VIBRATORY MOTORS** FOR CONSISTENT, HIGH-PERFORMANCE SCREENING
-  **LINEAR MOTION DESIGN** FOR EFFICIENT SOLIDS CONVEYANCE AND SCALPING
-  **ADJUSTABLE DECK ANGLE** FOR OPTIMIZED MATERIAL FLOW AND SEPARATION
-  **SKID-MOUNTED DESIGN** FOR EASY INSTALLATION AND INTEGRATION
-  **THREE-SCREEN DECK** PROVIDES 24 FT² OF SCREENING AREA FOR EFFICIENT, HIGH-CAPACITY SOLIDS REMOVAL

TRIFLO INTERNATIONAL RESERVES THE RIGHT TO MAKE CHANGES IN ENGINEERING, DESIGN AND SPECIFICATIONS; ADD IMPROVEMENTS; OR DISCONTINUE MANUFACTURING AT ANY TIME WITHOUT NOTICE OR OBLIGATION. EQUIPMENT AND DEPICTIONS SHOWN ARE FOR ILLUSTRATIVE PURPOSES ONLY AND MAY DISPLAY OPTIONAL ACCESSORIES OR COMPONENTS SPECIFIC TO CERTAIN MARKETS OR REGIONS.

© 2026 TRIFLO INTERNATIONAL. ALL RIGHTS RESERVED. PRINTED IN THE U.S.A. PLEASE RECYCLE

WWW.TRIFLO.COM

